



Conformity attestation

date: 15/04/2011

number: 57

Altaeco S.p.A. via G. Pascoli 4/6 - 20010 Vittuone (MI)

Plant address: via Pordenone, 13 - Oderzo (TV)
Year in which the mark was affixed: 2011
Reference standard: EN 14411
Product classification: Ceramic tiles dust pressed for
internal/external floorings
(glazed)
Series name: Appiani
Product name: Anthologhia antisdrucchiolo AS
Product description: TUTTI I FORMATI
Group: BI b (0,5% < E <= 3%)

CHARACTERISTICS

Reaction to fire: A1 / A1 fl

Flexural tensile strength:

breaking strength >	>1.700	N	(for tiles with thickness <= 7,5 mm)
breaking strength >		N	(for tiles with thickness > 7,5 mm)
modulus of rupture >	>45	N/mm ²	

Resistance to thermal shocks: passed

Bond strength/adhesion:

with cementitious adhesives	(cl.)	N/mm ²	NPD
with dispersion adhesives	(cl.)	N/mm ²	NPD
with reaction resines adhesive	(cl.)	N/mm ²	NPD
with mortar			NPD

Slipperiness:

declared value	R 10	- test method	DIN 51130
declared value	B	- test method	DIN 51097

declared value 1) = $\mu > \text{NPD}$ 2) = $\mu > 0,48$ -test method B.C.R.A. 1) = dry (leather); 2) = wet (rubber)

Skid resistance:

declared value NPD

Durability - freeze / thaw cycle: passed

Release of dangerous substances:

release of Cadmium	NPD	mg/dm ²
release of Lead	NPD	mg/dm ²